CHAPITRE 1

Proof Of Correctness (Sections 1.6, 2.3)

1.1. Introduction

> "Beware of bugs in the above code ; I have only proved it correct, not tried it."
>
> Donald E. Knuth `http://www-cs-faculty.stanford.edu/~knuth/`

How to check if a program is correct ?

Why checking if a program is correct ?

What is a correct program ?

DÉFINITION. *Specification* : precise description of how a program should behave.

A program is *correct*, if it behaves in accordance with its specifications.

How to check if a program is correct ?

- Testing
  - Designing good test data sets
  - You can prove there is a bug. No proof of no bug !
- Proof of Correctness

1.2. Correctness

1.2.1. Assertions.

```
...
x=sqrt(r) ;  // r should be >= 0 !
x=a[i] ;     // i should be in the correct range
...
```

DÉFINITION. *Assertion* : condition on the variables of a program that should be verified at some given step, if the program is running correctly.

Using assert in C/C++ :

```
#include <assert.h>
  ...
  assert(r>=0) ;
  x=sqrt(r) ;
  assert((0<=i) && (i<MAX)) ;
  x=a[i] ;
  ...
```

Each assertion is automatically checked :

– If the assertion is not verified, the program stops immediately with a message like :

```
Assertion failed, line 35 of file foo.c
```

– That's more informative for the user than a segmentation fault at the following line.
– This can be deactivated by adding a #define NDEBUG preprocessor directive.

With C++, java and other languages, you can use *exceptions* instead of assert :

– More informative error messages
– Error recovery mechanisms

Static type checking also makes some kind of assertion checking.

One way or the other, *check assertions in your programs.*

1.2.2. Specification of a function :

```
int factorial(int n) ;
// Preconditions : n is a non-negative integer
// Postcondition : returns n!
...
int factorial(int n) {
  assert(n>=0) ;
  if (n==0) return 1 ;
  return n*factorial(n-1) ;
}
```

The specification of a program can be formalized as follow :

– P : program
– X : input
– $P(X)$: output
– Q : precondition : predicate $Q(X)$ on the input
– R : postcondition : predicate $R(X, P(X))$ on the input and the output

Exemple. Program to compute of a square root

– P : $y := \text{sqrt}(x)$;
– X : x
– $P(x)$: y
– $Q(x)$: $x \geq 0$
– $R(x, y)$: $y^2 = x$

Définition. P is *correct* if $(\forall X)\ Q(X) \rightarrow R(X, P(X))$.

A *Hoare triple* is just a short hand notation : $\{Q\}\ P\ \{R\}$

Exemple. $\{x \geq 0\}\ y := \text{sqrt}(x);\ ;\ \{y^2 = x\}$

1.3. Proof of Correctness

1.3.1. Divide and Conquer. Let P be a big program :

s_0
s_1
s_2
$\dots$
s_{n-1}

To prove $\{Q\}\ P\ \{R\}$, we break P into elementary steps, and insert assertions that describes the state of the program at each step :

$\{Q\}$
s_0
$\{R_1\}$
s_1
$\{R_1\}$
s_2
$\dots$
s_{n-1}
$\{R\}$

P is correct, if each step is correct, i.e. the following Hoare triples hold :

- $\{Q\}\ s_0\ \{R_1\}$,
- $\{R_1\}\ s_1\ \{R_2\}$,
- $\dots$
- $\{R_{n-1}\}\ s_{n-1}\ \{R\}$

To prove that the elementary steps are correct, we will use some syntactic rules, exactly as we did in formal logic.

1.3.2. Assignment rule : Consider the following Hoare triple : $\{Q\}\ x := e\ \{R\}$

THÉORÈME. *If from Q you can derive R with x substituted everywhere by e, then the Hoare triple is valid.*

EXEMPLE. $\{x = 2\}\ y := x + 1\ \{y = 3\}$

When substituting, $y = 3$ becomes $x + 1 = 3$.

From $x = 2$, you can deduce $x + 1 = 3$.

So this Hoare triple holds.

EXEMPLE. $\{x > 0\}\ x := x + 1\ \{x > 1\}$

Here it can be confusing.

The same name x stands for both the value of x before and after the assignments.

If you get confused, just rename the variable :

$\{x_0 > 0\}\ x_1 := x_0 + 1\ \{x_1 > 1\}$

When substituting, $x_1 > 1$ becomes $x_0 + 1 > 1$, which you can deduce from $x_0 > 0$.

1.3.3. Conditional Rule. Consider the following Hoare triple :

```
{Q}
if condition B then
  P1
else
  P2
end if
{R}
```

THÉORÈME. *If the Hoare triples $\{Q \wedge B\}\ P_1 \{R\}$ and $\{Q \wedge B'\}\ P_2\ \{R\}$ hold, then the Hoare triple above holds.*

EXEMPLE. [?, Exercise 11 p. 78]

1.3.4. Loop Rule. Consider the following Hoare triple :

```
{Q}
while condition B do
  P
end_while
{R}
```

$\{Q\}$ describes the state of the program before the loop.

We need to have a predicate which describes the state of the program DURING the loop :

The *loop invariant* $\{S\}$

Most of the time, $\{Q\}$ will do the job, but not always.

THÉORÈME. *If the Hoare triple $\{S \wedge B\}\ P\ \{S\}$ holds, then the following Hoare triple will hold :*

```
{S}
while condition B do
  P
end_while
{S ∧ B'}
```

1.3.5. A simple example. Consider this little program :

```
Product(x,y)
// Precondition : x and y are non-negative integers
// Postcondition : returns the product of x and y
begin
  i :=0 ;
  j :=0 ;
  while ( (i=x)' ) do
    j=j+y ;
    i :=i+1 ;
  end while
  // Assertion : { j = x*y }
  return(j) ;
end ;
```

It's pretty clear that this algorithm it's correct.
Let's check it anyway to see how it works.

DÉMONSTRATION. We need a loop invariant, which will describe the state of the program after k iterations.
A reasonable guess is $S : j = iy$
Let i_k, j_k and S_k be the value of i, j and S after k iterations.
Base case : using the assignment rule, $i_0 = 0$ and $j_0 = 0$ so S_0 holds.
Induction step :
Assume the invariant holds after $k-1$ iterations : $j_{k-1} = i_{k-1}y$
We need to prove that the invariant is preserved by the k th iteration.
Otherwise said, we have to check that the following Hoare triple holds :

$$\begin{array}{l} \{S_{k-1} \wedge (i = x)'\} \\ \ j_k := j_{k-1} + y \ ; \\ \ i_k := i_{k-1} + 1 \ ; \\ \{S_k\} \end{array}$$

Let's applying the assignment rule.
By substituting i_k and j_k by the expressions they have been assigned with, we get :

$$\begin{array}{rclcll} S_k & \Leftrightarrow & j_k & = & i_k y & \\ & \Leftrightarrow & j_{k-1} + y & = & (i_{k-1}+1)y & \text{(By the substitution rule)} \\ & \Leftrightarrow & i_{k-1}y + y & = & (i_{k-1}+1)y & \text{(By } S_{k-1}\text{)} \\ & \Leftrightarrow & i_{k-1}y + y & = & i_{k-1}y + y & \end{array}$$

So, S_k indeed holds.
By induction, after any number k of iterations, S_k still hold.
At the end, both S_k and $i = x$ hold, so, as expected : $j = iy = xy$ □

REMARQUE. We have proved that after the end of the execution the result is correct.
But what if the program does not terminate and loop forever ?
This is not usually consider a proper behavior.
We only have spoken about *partial-correctness*.
A full proof of correctness needs also a proof of termination !

1.3.6. A more sophisticated example : The Euclidean algorithm.

```
GCD(a,b)
Begin
// Precondition : a and b are non-negative integers
// with a>=b.
// Postcondition :
// returns gcd(a,b), the greater common divisor of
// a and b.
Local variables : i, j, q, r
  i :=a ;
  j :=b ;
  while j>0 do
    // Assertion :
```

```
      // r is the rest of the integer division i/j
      r := i mod j ;
      i := j ;
      j := r ;
    end while
    // Assertion : i is the gcd of a and b.
    return(i) ;
  end ;
```

EXERCICE 1. Use the Euclidean algorithm to compute :
`GCD(8,8)`, `GCD(14,4)`, `GCD(31,17)`.

Here the proof of correctness of the algorithm is non-trivial.

DÉMONSTRATION. Let i_k and j_k be the value of i and j after k iterations. We need to find an invariant which describes the state of the program after each iteration.
Take S_k : $\gcd(i_k,\ j_k) = \gcd(a, b)$.

(1) Base case :
Before the loop, $i_0 = a$ and $j_0 = b$.
So the invariant S_0 holds : $\gcd(i_0,\ j_0) = \gcd(a, b)$;

(2) Induction step :
Assume S_{k-1} holds, that is $\gcd(i_{k-1},\ j_{k-1}) = \gcd(a, b)$.
We just need to prove that $\gcd(i_k,\ j_k) = \gcd(i_{k-1},\ j_{k-1})$.
By the assignment rule, we have :
– r is the rest of the division of i_{k-1} by j_{k-1},
– $i_k = j_{k-1}$,
– $j_k = r$.
So, by the definition of the integer division, we have :

$$i_{k-1} = qj_{k-1} + j_k$$

for some integer q.

(a) Assume x divides both i_k and j_k.
Then, of course j_{k-1}, since $j_{k-1} = i_k$.
By the equation above, x also divides i_{k-1}.

(b) Assume x divides both i_{k-1} and j_{k-1}.
Then of course x divides i_k.
Once again, using the equation above, x also divides j_k

Therefore, $\gcd(i_k,\ j_k) = \gcd(i_{k-1},\ j_{k-1}) = \gcd(a, b)$, as wanted.

(3) At the end :
By induction, the loop invariant S still holds : $\gcd(i,\ j) = \gcd(a, b)$
Moreover, the loop condition failed : $j = 0$.
So, $\gcd(a, b) = \gcd(i,\ j) = \gcd(i,\ 0) = i$, as expected.

□

1.4. Conclusion

1.4.1. A note on automatic program proving :

- There is no mechanical way to decide even if a program terminates or not.
- Traditional imperative languages :
  - Automatic proving is very difficult because of *side effects*
  - side effects needs to be considered as some form of output
- Functional languages (lisp, scheme, ML, caml) :
  - Designed to make it easier to prove correctness
  - Fun to program. Try them !
- Two difficulties :
  - Finding the correct assertions
  - Checking that the implications holds
- Mixed approach :
  - The programmer gives the main assertions
  - The prover derives the other assertions

1.4.2. Check assertions in your programs !

- Use static type checking / assert / exceptions
- When debugging, you can ask for all assertions to be checked
- Documentation
- Help for the proof